

NeoDiamond[®] Non-Sterile, Diamond Discs Instructions for Use

CAUTION:

The device is to be used as per the following instructions by physician or licensed practitioner Rx Only. These instructions, in whole or in part, are not a substitute for formal training. Appropriate professional education is STRONGLY RECOMMENDED prior to using this device clinically.

DESCRIPTION:

The HP Diamond Discs are a rotary abrading device made of stainless steel coated with diamond particles on the working end and designed to fit into a dental handpiece. The handpiece connection provides the rotation, allowing the user to abrade hard structures like metal, plastics, porcelains, and similar materials. The HP Diamond Discs are provided non-sterile and can be reused, therefore read the following cleaning and sterilization instructions carefully.

The HP Diamond Discs intended to be used by professional dentists and dental technicians in the dental laboratory.

The HP Diamond Discs are provided mechanically clean, but non-sterile and may be reused following cleaning and sterilization instructions as described in this IFU.

INDICATIONS

Microcopy HP Diamond Discs are intended to be used by dentists in dental clinics/hospitals/labs for the removal of small amounts of outer substrate surface between two adjacent structures (Interproximal reduction). It is a means to acquire additional space to create ideal tooth alignment.

CONTRAINDICATIONS TO USE

- a) Used HP Diamond Discs shall be considered as contaminated and as such, appropriate precautions shall be taken during re-processing and disposal. Suitable eye protection, glove and a mask should be worn when re-processing.
- b) In the event of an HP Diamond Disc will be returned to Microcopy, please ensure any contaminated and/or potentially contaminated HP Diamond Disc have been effectively cleaned and are appropriately packaged for return.

STORAGE

Store in a dry and clean environment at ambient temperature.

PRECAUTIONS:

- a) Carefully read package labels to ensure appropriate use of the HP Diamond Disc. Failure to do so may cause procedural delays or user injury.
- b) Failure to follow these instructions may cause the following: preparation site damage and injury to the user.
- c) Clean and sterilize the HP Diamond Disc supplied in a non-sterile condition in accordance with the directions below before first use and before each reuse.
- d) Always wear gloves when handling contaminated instruments.
- e) Clinicians should wear eye protection and facemask when using the HP Diamond Disc.
- f) Surgical masks shall be worn to avoid inhalation of aerosol and/or dust generated during the procedure.
- g) Prior to use inspect the HP Diamond Disc for broken and/or damaged grit, discard any potentially defective burs. Do not use worn-out or dull devices.
- h) Ensure handpieces are maintained in good working order and remain correctly lubricated at all times.
- i) Discard any damaged HP Diamond Disc immediately.
- j) Do not use rusted HP Diamond Disc.
- k) Carefully read the labels on the package.
- I) Follow the hand piece manufacturer's instructions for use and maintenance and service all hand pieces appropriately.
- m) Before use, run the handpiece to check for any abnormalities including overheating.



- n) Do not apply excessive pressure on the HP Diamond Discs this could cause undesirable heat and/or may cause the HP Diamond Disc to fail.
- o) Move the disc continuously when in use to avoid localized heating and/or damage to the bur.
- p) Maintain handpieces in good working condition to ensure maximum effectiveness of the device. Failure to properly maintain handpieces may lead to procedural delays or injury to the user or damage to the preparation site due to vibration of a worn chuck or turbine.
- q) Ensure the disc is fully seated and securely gripped in the handpiece collet prior to use. Failure to do so may cause the device to "walk out" of the handpiece and may lead to injury of the user.
- r) Never force a HP Diamond Disc into a handpiece as this could cause damage to the handpiece collet which could result in procedural delays.
- s) Never exceed the maximum speeds as shown in the table as this may generate undesirable heat.
- t) Do not exceed the maximum speeds tabulated below:

Instrument head diameter	Maximum permissible speed		
01/10 (mm) – ISO	(RPM)		
100 - 127	30,000		
130 - 300	25,000		

REPROCESSING INSTRUCTIONS FOR HP DIAMOND DISCS

Limitations of Re-Use

Reprocessing will have little effect on Microcopy's HP Diamond Discs. The bur shelf life is determined by wear and damage in use and the burs should be inspected for defects during the preliminary cleaning process.

Delay between use and reprocessing must be kept to minimum to avoid contaminants drying, thereby making cleaning more difficult. Therefore, keep the unclean discs immersed in the cleaning/disinfecting agent in accordance with its manufacturer Instructions, but in any event do not exceed 12 hours.

Caution: Do **not** leave discs immersed in disinfectants that have a fixative action (such as aldehyde-based products) unless the burs have been thoroughly cleaned first.

WARNINGS

Used HP Diamond Discs should be considered, as being contaminated and appropriate handling precautions should be taken during reprocessing. Gloves, eye protection and a mask should be worn. Used HP Diamond Discs are considered bio-hazard and need to be discarded as bio-hazard waste unless reprocessing.

CLEANING, DRYING, AND INSPECTION PROCEDURE FOR LABORATORY USE

Manual Cleaning:

If manual cleaning is implemented, the HP Diamond Discs should be cleaned in a sink dedicated for the purpose. Microcopy has validated the procedure detailed below:

- 1. Rinse the instruments under running cold water and keeping them immersed. Brush thoroughly away from the body using a neutral cleaning or cleaning/disinfecting agent labeled for use on dental discs or other similar types of reusable medical instruments, following the agent manufacturer's instructions.
- 2. Care should be taken to avoid spreading contaminants by spraying or splashing during the brushing process.
- 3. Wire brushes must be used with caution, as brass particles may result in galvanic corrosion and steel particles may cause discoloration of stainless steel.
- 4. After cleaning, inspect the instruments, preferably with the aid of magnification, to ensure that all contamination has been removed. Repeat the cleaning process if necessary



- 5. Dry the instruments using paper toweling or dry heat not exceeding 140°C
- 6. After cleaning, inspect the instruments, preferably with the aid of magnification, to ensure that all contamination has been removed. Repeat the cleaning process if necessary.

Steam Sterilization:

<u>Scope</u>

These sterilization instructions are applicable to HP Diamond Discs initially provided non-sterile and to non-sterile discs that are about to be reused.

Packaging for Sterilization

If using an autoclave with a pre-vacuum cycle, pack the discs in dedicated instrument trays or pouches validated for steam sterilization.

If using an autoclave without a pre-vacuum cycle, the discs should not be packed or wrapped but should be contained in dedicated disc stands with perforated lids.

Note: Local legislation may require that burs/discs will be wrapped in pouches for processing in either type of autoclave. <u>Sterilization Process</u>

Follow the autoclave manufacturer's instructions to sterilize the discs. Care must be taken not to exceed the maximum recommended load for the autoclave.

Microcopy has validated steam sterilization in an autoclave without a pre-vacuum cycle (gravity displacement type) for a holding time of 10 minutes at a temperature of 135 °C and 30 minutes drying. The holding time is the minimum time for which the minimum temperature is sustained.

Note: Local infection control practice may recommend a different combination of holding time and temperature.

<u>Storage</u>

The HP Diamond Discs should be stored in the sterilization container (bur stand or pouch) until use. Containers or pouches must be dried before opening to avoid recontamination of the contents with water. Storage should be in dry, clean conditions and at ambient temperature.

Validation of Cleaning and Steam Sterilization

The above detailed processes have been validated as being Microcopy recommended process for preparing Microcopy's dental discs for reuse. It remains the responsibility of the repressor to ensure that the reprocessing as actually performed, using the equipment, materials, and personnel in the reprocessing facility, achieve the required results. This may require validation and monitoring of the process. Any deviation from these instructions should be properly evaluated for effectiveness and potential adverse results.

TRACEABILITY:

Each package includes **Lot number LOT** on its label. This number must be quoted in any correspondence regarding the product.



APPLICABLE SYMBOLS:

	Manufacturer	Indicates the medical device manufacturer.	ī	Consult instructions for use	Indicates the need for the user to consult the instructions for use.
REF	Catalog Number	Indicates the manufacturer's catalog number so that the medial device can be identified	LOT	Batch Code	Indicates the manufacturer's batch code so that the batch or lot can be identified.
EC REP	Authorized European representative	Indicates the Authorized representative in the European Community.	CE	CE Marking	Indicates European Conformity Mark.
NON	Non-Sterile	Indicates a medical device that has not been subjected to a sterilization process.	RxOnly	DEVICE for professional use only	(ref US FDA CDRH) Indicates device shall only be used by a trained professional.
MD	Medical Device	Indicates device is designed and intended for medical use.		Importer	Indicates the entity importing the medical device into the locale

CONTACT INFORMATION:



Microcopy

3120 Moon Station Rd. NW Kennesaw, GA 30144, USA sales@microcopydental.com 800.235.1863



Obelis s.a.

Bd. Général Wahis 53 1030 Brussels, Belgium <u>mail@obelis.net</u> + (32) 2. 732.59.54



REVISION HISTORY:

MCD-IFU-017 Rev: 2 Date of Issue: 20May2021